

XL MFG: MINI DECK



- 12" loaded deck height for tall loads
- Steel flooring on center deck, Apitong on outer bays
- Unique 3 beam deck design is light and strong
- Deck uses 4" junior I-beams on 18" centers
- · Full-width platform adds loading space
- 12 d-rings provide tie-down locations
- Front ramp tapers to four inches



RUGGED & VERSATILE MAIN DECK

XL HDG Mini-decks feature a 12" loaded deck height with 4" of ground clearance. XL Mini-decks are available in capacities from 60,000 pounds to 80,000 pounds, with base weights as low as 16,500 pounds. They come in both 48' long and 53' long - with 29' or 34' in the well, respectively.

AIR OPERATED HATBOX OPTION

The mechanical gooseneck with an air bag hatbox allows the user to raise and lower the deck to clear obstructions and adjust to the tractor's fifth wheel height without the use of hydraulics. Adjust the air operated hatbox to your desired height, and simply secure with lock pins.

DESIGNED FOR YOU. BUILT TO LAST.





XL 60 MFG: MINI CAPACITY

capacity: 60.000 lb overall concentrated: 60,000 lb in 16' closed

XL 70 MFG: MINI CAPACITY

capacity: 70,000 lb overall concentrated: 70,000 lb in 16' closed

XL 80 MFG: MINI CAPACITY

capacity: 80,000 lb overall concentrated: 80,000 lb in 16' closed

OVERALL LENGTH & WIDTH

overall length: 48' or 53' overall width: 102"

STANDARD GOOSENECK

mechanical detachable full-width 10' long

49" 5th wheel height

84" swing clearance

16" king pin setting

2 bent d-rings per side

1 1/8" Apitong decking - flush

frame reinforcement for flip neck

AIR HATBOX OPTION

mechanical detachable full-width 10' long

40" - 52" 5th wheel height,

12" of travel

82" swing clearance

18" king pin setting

2 bent d-rings per side

11/8" Apitong decking -flush

aluminum mudflaps

OTHER GOOSENECK OPTIONS

pan style d-rings double donuts

36" flip neck extension

MAIN DECK

48' version: 29' long 53' version: 34' long T-1 flange, 80K web (2) 8" fabricated i-beams center box beam 12" loaded deck height 4" ground clearance

4" jr i-beam cross members on 18" centers 80 only: mid-header

12 bent d-rings per side

1 1/8" Apitong decking - flush in outer bays

steel floor in center deck

ramp tapers to 4"

MAIN DECK OPTIONS

13/8" Apitong decking - raised additional clearance lights

4-way plug(s)

chain drops

additional d-rings

Durabek non-slip on center deck

REAR BRIDGE

9' long

40" deck height

1 1/8" Apitong decking flush

2 flag holders

2 bent d-rings in tail channel

2 pair pan-style d-rings, on corners frame reinforcement for flip axle

REAR BRIDGE OPTIONS

clearance lights

pull out lights

4" amber strobe tail light

additional tail light

battery back up

(1) 4-way plug

13/8" Apitong decking - raised dock bumpers

SUSPENSION

25.000 lb air ride raise and lower valve manual ride height control

SUSPENSION OPTIONS

liquid filled air gauge air weigh digital scale control in aluminum box - ball valves electric dump valve with 4-way plug and wire

AXLES

(2) 25.000 lb nominal hub pilot, outboard drums 4S2M ABS 16 1/2" x 7" brakes (2) pair spring brakes

AXLE OPTIONS

PSI tire inflation system hubometer

TP axles (same inner & outer bearings)

WHEELS & TIRES

8.25 x 22.5 steel rims 255 / 70R / 22.5 tires

WHEEL & TIRE OPTIONS

aluminum mill wheels (inside) aluminum mill wheels (outside) aluminum polished wheels (outside) aluminum Durabright wheels (outside)

Michelin 255/70R/22.5 tires

LIGHTING

12V sealed Grote harness rubber mounted LED lights 2 tail light package with aluminum cover 2 clearance lights per side

1 mid-turn light per side

7 pole electric socket

PAINT

black, IH red, CAT yellow air & electric done after paint

PAINT OPTIONS

non-standard paint colors non-standard metallic paint

WARRANTY

5 year structural 1 year paint

AVAILABLE MODELS

XL 60 HDG: Mini-deck XL 70 HDG: Mini-deck XL 80 HDG: Mini-deck