


DorseyTrailer.net 334.897.2525 ELBA, AL



Generations of skilled craftsmen in Elba, Alabama take pride in building a full line of trailers that meets the road's demands. People make the difference at Dorsey, putting quality first in every step of the manufacturing process.











80.000 lbs GVWR (52.000 lbs in 4')

WEIGHT

CAPACITY

11.250 lbs +/- 3%

LOAD BASE

12 Pair "J" Handles - Double "L" Track - 12 Pair Winches - C/S Tie Bar

DIMENSIONS

Overall: 102" width x 48' or 53' length

Coupler Height: 48"

KING PIN

2" AAR • Setting: 24"

MAIN BEAMS

Fabricated I-Beam with All Aluminum Neck Design — 6061 T-6 Aluminum

FLANGES

Extruded — Aluminum 6061-T6

WEB

Aluminum 5083

FRONT & REAR SKIRT

Extruded Aluminum 6061-T6 – Integrated Stake Pockets on Rear

BUMPER

US DOT and Transport Canada Compliant Rear Impact

CROSS MEMBERS

5" Aluminum 6061-T6 on 15" Centers (22" Option)

HEAVY DUTY COIL PACKAGE

4' Span, Center of Trailer

SIDE RAIL

Extruded Side Rail with J-Hook Integration and Bolt-On LL Track — Road and Curb Side

PIIR PAII

3/8" X 3" Aluminum with Recessed Conspicuity Tape

STAKE POCKETS

Aluminum 6061-T6 — 24" Centers

PIPE SPOOL

H.D. Extruded Pipe Spool Design for More Durable Siderail

FL OOR

1-1/2" Multi-Hollow Core Extruded Aluminum 6061-T6 with 2 Nailers

DorseyTrailer.net
334.897.2525 ELBA, AL

LOAD SECUREMENT

12 Pair "J" Handles - Double "L" Track – 12 Pair Winches

AIR TANK

All Aluminum

MUD FLAPS

Heavy Duty, Black, Anti-Spray, Anti-Sail

FINISH

Natural Aluminum Finish with Aluminum Landing Gear and Galvanized Suspension

ALUMINUM GIANT • AF-LH

LIGHTIN

Grote Ultra Blue[™] – Sealed Wiring Harness – Grote [™] High Count LED Lights

LANDING GEAR

Heavy Duty – Aluminum – 2-Speed Gear Drive, 140,000 lbs Static Load Capacity

SUSPENSION

Air Ride, 23,000 lbs Capacity, Galvanized

AXLES

Heavy Duty, 23,000 lbs Capacity

BRAKES

Brakes: 16 1/2" X 7" Quick Change

ABS Brakes: 2S/1M

Brake Drums: Standard Cast, Outboard Mount

HUB

Standard Cast, Hub Piloted, 10-Stud Unimount, Oil Lubricated

WHEELS

Hub Piloted Aluminum – Mill (Inside) & Polished (Outside)

TIRE

255/75R22.5 Double Coin Radials

OPTIONS

- Heavy Duty Beam Packages
- Lift Axles
- Intermodal Container Twist Locks
- Toolbox(es): Aluminum
- Strobe Lights
- Wide Load Lights
- Custom Light Package
- Hubodometer
- Tire Inflation System
- Bulkhead: Aluminum
- RAS Rear Axle Slider Suspension
- Recessed Chain Ties
- 17.5 Wheels

Note: All specifications are subject to change without prior notification. All dimensions and weights are approximate. Trailers pictured in this brochure may feature optional equipment. Axle placement and legal load ratings are dependent upon federal, state, and local regulations, GAWR and tire ratings. Copyright © 2020 Pitts Enterprises, Inc. (published). All rights reserved.