


20'/40' SL COMBO TRIDEM



Carries one (1) 20' loaded, one (1) 40' loaded or two (2) 20' empty ISO containers.
Meets all TOFC, AAR, DOT, FMVSS, ISO, ANSI, SAE and TTMA specifications.




**LEADING THE INTERMODAL
EVOLUTION**

10530 Sessler St / South Gate, CA 90280 / Telephone: 877-711-0725



FUNCTION

Carries one (1) 20' loaded, one (1) 40' loaded or two (2) 20' empty ISO containers. Meets all TOFC, AAR, DOT, FMVSS, ISO, ANSI, SAE and TTMA specifications.



DIMENSIONS

Overall Length:	40' 11" extended / 31' 7" retracted (Excludes rear bumper)
Overall Width:	96"
Fifth Wheel Height:	47"±1"
Rear Deck Height:	48"±1"
Kingpin Location:	17'-1/2" (From rear face of front bolster)
Axle Spread:	61"
Tridem Location:	25" (From rear face of rear bolster to rear axle center)
Tare Weight:	10,600 Lbs (±2%)
Gross Vehicle Weight Rating:	77,000 Lbs for 20' loaded / 85,000 Lbs for 40' loaded

STEEL STRUCTURE & COMPONENTS

Material:	High strength GR50, GR80 and GR130 steel.
Painting:	2 coat paint system - 2k Epoxy Primer with 2k Polyurethane top coat 5-Year Warranty (color black).
Main Beam:	16" x 5" fabricated I-beam with high strength flanges, 6-11/32" height for GN rail.
Slider Beam:	14-3/4" deep x 5" wide fabricated I-beam, 2-pin locking system.
Crossmember:	Fabricated channel type not less than 3/16" thick.
Upper Coupler:	1/4" thick w/ 2" dia. drain holes, reinforced by 1/4" thick channel type kingpin supports. HOLLAND or JOST 2" AAR certificated kingpin.
Rear Bolster:	6-5/8" height x 4" wide fabricated box beam bolster with flip-up twist locks.
Twist Lock:	Buffer or TOCA compact retractable twist locks.
Landing Leg:	JOST A440 Series.
Suspension:	Hutch tridem underslung mechanical suspension.
Axle/Wheel Ends:	Meritor.
Slack Adjuster:	Haldex 5.5" ASA
Lubricant:	Stemco seal, Mobilith SHC 007 synthetic grease lubricant with metal Stemco or National hub cap.
Hub & Drum:	10 stud hub piloted hubs with outboard mounting cast steel drum.
Tire/Steel Wheels:	Westlake 255/70R22.5 or Ling Long equivalent. Jingu 8.25 x 22.5 steel or Accuride, Sunrise equivalent, White.
Brake Chambers:	Haldex 3030 2.5" stroke
ABS/ECU:	Wabco 4S/2M ABS brake system.
Lights/Harness:	Phillips.
MISC:	CIEM Standard Markings, Conspicuity tape, Document holder, 24" x 18" Black rubber mud flap with CIEM logo.
Option:	Tire inflation system.